

Completes the Smartness

Combine outstanding RFID performance with your Smart Device for a seamless UHF RFID experience. With Nordic ID EXA51e retail and logistics markets receive a powerful UHF RFID reader that is compatible with all common operating systems.

What makes Nordic ID EXA51e so powerful is the new Nordic ID NUR2-1W module. Nordic ID EXA51e is easily connected to any Smart Device via Bluetooth low energy and it offers multiple secure fastening options.

The powerful reading performance and long battery life make Nordic ID EXA51e ideal for heavy-duty inventory tasks e.g. in retail and POS.



PRODUCT VARIANTS

WIRELESS CHARGING



QUAD LOCK



RFID IDENTIFICATION	
Supported standard	ISO 18000-63 (EPC Class 1 Gen2)
Frequency	ETSI 865.6–867.6 MHz or FCC/IC 902–928 MHz
RF radiated power	ERP 2W/EIRP 3.3W
Antenna features	Software controlled antenna modes: linear (horizontal & vertical), circular and proximity Nominal reading distance: Linear polarization mode 10 m/33 ft, circular polarization mode 6 m/20 ft, proximity mode, read range down to 1 cm/0.4 inch
Max receive sensitivity	-77 dBm
Typical reading speed	Up to 1000 tags/s
BARCODE IDENTIFICATION	
2D imager	All major 1D barcodes and 2D codes High visibility LED aimer 2 character pre and post fixes, padding, replacement Enhanced aiming mode (automatic switching between scan line / aiming dot) Configurable scan alert sounds
PLATFORM	
RFID	Nordic ID NUR2-1W reader module
Operating system	Embedded IoT platform
USER INTERFACE	
Keys	Power and Unpair a Bluetooth device Trigger button

PRODUCT HIGHLIGHTS

- Cutting edge UHF RFID reading sensitivity and reading speed
- Effortlessly connect any existing smart device to the RFID reader via Bluetooth Low Energy
- Ergonomic design due to lightweight and balanced weight distribution
- Effortless and secure locking mechanism for smart devices
- Operates a full working day on a single charge
- Nordic ID Smart Pair for effortless connectivity

SUPPORTED OPERATING SYSTEMS

- Android 5.0 or newer
- iOS 9 or newer
- Windows 10 (UWP)

Note: Bluetooth Low Energy needs to be supported by host device

SOFTWARE DEVELOPMENT ENVIRONMENTS

- Android Studio
- Apple Xcode
- Microsoft Visual Studio
- Source code available at: <https://github.com/NordicID>

User feedback	3 LEDs and buzzer		
COMMUNICATION			
Wireless PAN	Bluetooth 4.2 (Low Energy) Class 2 Supported profiles: GATT, HID		
POWER			
Battery	Rechargeable, removable Lithium-Ion battery pack 7000 mAh, 3.7V Up to 14 h in intensive use		
Charging of EXA51	Charging over cradle (0 to 100 %) 5 h Charging over micro USB connector (0 to 100 %) 5–10 h		
Charging of host device	Qi wireless charging supported (not available in Quad Lock version) Maximum charging power 5 W Charging from cradle via USB cable Adaptive charging power (4–7W) based on charge level of EXA51 battery		
External power supply	AC adapter for desktop charger: input 100–240 VAC, 1 A, 50–60 Hz / output 5.2 VDC, 3 A, 15 W / Power adapter for EU, UK or US		
SIZE AND WEIGHT			
Dimensions	(H) 196 x (W) 83/91 x (D) 21/135 mm (H) 7.7 x (W) 3.3/3.6 x (D) 0.8/5.3 inch		
Weight	490g / 17.3 oz		
DROP AND SHOCK			
Drop and impact resistance	1.5 m / 4.9 ft		
ESD	Contacts	+/- 4kVdc	
	Air discharge	+/- 8kVdc	
ENVIRONMENT			
Temperature	Operating	-20 to +55 °C	-4 to +131°F
	Storage	-20 to +60 °C	-4 to +140 °F
	Charging	0 to +45 °C	+32 to +113 °F
Relative humidity	10 % to 95 % non-condensing		
Fastening options	Magnets, screws or Quad Lock (not available in wireless charging version)		
Environmental sealing	IP54		
Inbox content	Nordic ID EXA51e, counter parts of magnets, screws and Safety & Regulations guide		

ENVIRONMENT

- Maintenance service and extended maintenance contract
- Software customization and development support
- Technology, product and integration training
- Technology and project consultation
- Project management services

WARRANTY

- 2 year warranty
- Free technical support during and after 2 year warranty



EU DIRECTIVE
2002/96/EC ON WASTE
ELECTRICAL AND
ELECTRONIC
EQUIPMENT (WEEE)

All information is subject to change without prior notice. Availability of product variants may vary regionally.